



Darba vides  
Non-aggressive gases, dry, oil-free air  
Elektriskais pieslēgums  
Male connector M8, four pin  
Histerēze  
Adjustable: 3 to 25% of set value  
Izejas signāls  
Analogue: 1 to 5 V  
Korpuss  
Polycarbonate  
Mērīšanas vielas pieslēgums  
G 1/8 male and M 5 female  
Slēgšanas daudzums  
125 mA  
Slēgšanas funkcija  
PNP  
Strāvas patēriņš  
30 mA  
Temperatūras diapazons  
0 - 50 °C

## Apraksts

Universal electronic vacuum switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly on the suction pad. <br>Switching point and hysteresis adjustable with a screw. Integrated LED for indication of the switching state.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	G1	G2	G3	L mm	L1 mm	Mērīšanas diapazons	Slēgšanas daudzums mA	Spriegums	Strāvas patēriņš mA
K- 07 45 01 58	G 1/8"	M 5	M 8 x 1	44.0	62.0	-1 bis 0 bar	125	10.8 - 30 V DC	30