

K-INLINE-EJEKTTOREN VR

Inline ejectors »VR«, screw connection



Īpašības

No moving parts, which means no wear and no maintenance
Vacuum generator with high maximum vacuum level (85% vacuum)
ultra small footprint, suitable for confined spaces
minimal air consumption

low noise

Izmantošana

by screwing / plugging into the distribution beam direct attachment to the suction pad
for handling various workpieces

Korpuss

Aluminium eloxed (type VR)

Sprauslu sistēma

Brass (type VR)

Savienojums

Spraudsavienojums

Apraksts

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Sprauslu izmērs	Gaisa izvades pieslēgums	Saspiestā gaisa pieslēgums	Vakuuma pieslēgums	Iztukšošanas pakāpe	Sūkšanas gaisa patēriņš l/min	maks. sūkšanas apmērs l/min	Garums mm	Ekspluatācijas spiediens bar
K- 07 45 01 29	01	M 5 male	G 1/4 IG	G1/8 female	90 %	21.0	14.0	35.0	5.0
K- 07 45 01 30	01	M 5 male	G 1/4 IG	G1/8 female	89 %	36.0	21.0	35.0	5.0