



## Īpašības

Vacuum generator with integrated control valves and system monitoring functions  
Gripping and blowing off can be controlled without the need for external valves  
Optimised air consumption thanks to many models with differing suction capacities  
Minimum energy costs in continuous operation  
Easy adjustment with foil keypad and LED display of the settings  
Minimum size, low weight  
Optimum vacuum generation directly on the suction pad  
Complete solution for very simple installation  
Short learning curve thanks to "teach" function  
No need for additional sensors  
Easily visible status indication

## Izmantošana

Ideal where space is restricted and for highly dynamic movements, handling with industrial robots, linear axes pick-and-place systems

## Iztukšošanas pakāpe

85 %

## Pamatkorpuss

Anodised aluminium

## Iebūvēts

NC blow-off valve, filter, silencer, non-return valve

## Apraksts

Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Iztukšošanas pakāpe %	Sprauslu izmērs	Iesūkšanas vārsts miera stāvoklī	Saspīestā gaisa pieslēgums	Vakuuma pieslēgums	Sūkšanas gaisa patēriņš l/min	maks. sūkšanas apmērs l/min	Ekspluatācijas spiediens bar	
K- 07 45 01 46	85	01	NC	M 5 IG	M5 female	46.0	23.0	4.5	65 10 10
K- 07 45 01 45	85	01	NO	M 5 IG	M5 female	46.0	23.0	4.5	65 10 10