


**Modelis**

with pressure gauge and with high performance muffler, angled

Darba vides

Saspiests gaiss

min. ekspluatācijas spiediens

0,20 MPa

maks. ieejas spiediens

0,1 to 1,0 MPa

Pneimatisko manometru pieslēgumu skaits

2

Pneimatiskā manometra pieslēgums

Rc 1/8

Vides temperatūra

+2 °C bis +50 °C

Vielas temperatūra

+2 °C to +50 °C

## Apraksts

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

## Produkts

Apzīmējums	Pneimatisko manometru pieslēgumu skaits	Pneimatiskais pieslēgums	Caurpl_de nom. l/min	maks. ekspluatācijas spiediens MPa	Spiediena iestatišanas mehānisms	Spiediena pastiprināšanas process	Ti
K- 07 60 00 04	2	G 1/4	230	3.00	manually operated	1:2	1/4