


K-DVST MIT REGLER

Pressure booster with regulator

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Ieejas spiediens
2 - 10 bar
Izejas spiediens
Max. 20 bar (regulated: max. 16 bar)
Temperatūras diapazons
-10 °C to +50 °C (40 mm bore), -10 °C to +60 °C (63 mm bore)
Darba vides
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Blīvējums
NBR
Caurule
Anodised aluminium jacket
Korpuss
Aluminium, anodised
Spiediena regulators
With plastic body
Montāža
Any position, with 4 mounting holes
P2:P1
1:1 to 1.6:1

Apraksts

Pressure multipliers (boosters) allow a separate compressed air store with up to double pressure to be installed for selected devices in a compressed air system without an external energy source, i.e. it is possible to work with a maximum pressure of 20 bar in a standard 10 bar system (maximum ratio 2:1). This is achieved using a double piston, which is operated by a combination of integrated check valves in such a way that the booster works automatically until the target pressure is reached in a compressed air tank and is then automatically switched off. A tank is always required to build up the pressure and store the compressed air!

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	Ø virzulim mm	H mm	L mm
K- 07 25 08 65	G 1/8"	40.0	139.0	194.0
K- 07 25 08 67	G 3/8"	63.0	183.0	290.0