


K-DVST MIT REGLER

Pressure booster with regulator

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Ieejas spiediens

2 - 10 bar

Izejas spiediens

Max. 20 bar (regulated: max. 16 bar)

Temperatūras diapazons

-10 °C to +50 °C (40 mm bore), -10 °C to +60 °C (63 mm bore)

Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Blīvējums

NBR

Caurule

Anodised aluminium jacket

Korpuss

Aluminium, anodised

Spiediena regulators

With plastic body

Montāža

Any position, with 4 mounting holes

P2:P1

1:1 to 1.6:1

Apraksts

Pressure multipliers (boosters) allow a separate compressed air store with up to double pressure to be installed for selected devices in a compressed air system without an external energy source, i.e. it is possible to work with a maximum pressure of 20 bar in a standard 10 bar system (maximum ratio 2:1). This is achieved using a double piston, which is operated by a combination of integrated check valves in such a way that the booster works automatically until the target pressure is reached in a compressed air tank and is then automatically switched off. A tank is always required to build up the pressure and store the compressed air!

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	Ø virzulim mm	H mm	L mm
K- 07 25 08 65	G 1/8"	40.0	139.0	194.0
K- 07 25 08 67	G 3/8"	63.0	183.0	290.0