

K-DRG DRV 200 STANDARD

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNIECĪBA

DRV 200 pressure regulators, standard type



Ieejas spiediens
Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series)
Temperatūras diapazons
Max. 75 °C
Samazināšanas process
Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series)
Blīvējums
NBR
Atsperes korpuss
Pressed brass up to DN 25, Grey cast iron from DN 32
Korpuss
Red brass 2.1096.01

Apraksts

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C mm	D mm
K- 07 25 04 86	G 1/4	1.5 - 8 bar	0.5	70.0	167.0 mm	120.0	47.0
K- 07 25 04 87	G 3/8	1.5 - 8 bar	0.6	70.0	168.0 mm	121.0	47.0
K- 07 25 04 88	G 1/2	1.5 - 8 bar	1.2	85.0	188.5 mm	142.0	46.5
K- 07 25 04 89	G 3/4	1.5 - 8 bar	1.3	85.0	189.5 mm	143.0	46.5
K- 07 25 04 90	G 1	1.5 - 8 bar	1.6	95.0	242.0 mm	186.0	56.0
K- 07 25 04 91	G 1 1/4	1.5 - 8 bar	4.2	104.0	323.0 mm	262.0	61.0
K- 07 25 04 92	G 1 1/2	1.5 - 8 bar	4.5	108.0	323.0 mm	262.0	61.0
K- 07 25 04 93	G 2	1.5 - 8 bar	7.2	146.5	376.0 mm	306.0	70.0