

# K-DRG DRV 225 HOCHDRUCK

DRV 225 pressure regulators, high-pressure type



Ieejas spiediens  
Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series)  
Temperatūras diapazons  
Max. 75 °C  
Samazināšanas process  
Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series)  
Blīvējums  
NBR  
Atsperes korpuss  
Pressed brass up to DN 25, Grey cast iron from DN 32  
Korpuss  
Red brass 2.1096.01

## Apraksts

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m <sup>3</sup> /h	A mm	B	C mm	D mm
K- 07 25 04 97	G 1/4	1.5 - 20 bar	0.5	70.0	188.0 mm	141.0	47.0
K- 07 25 04 98	G 3/8	1.5 - 20 bar	0.6	70.0	188.0 mm	141.0	47.0
K- 07 25 04 99	G 1/2	1.5 - 20 bar	1.2	85.0	228.5 mm	182.0	46.5
K- 07 25 05 00	G 3/4	1.5 - 20 bar	1.3	85.0	228.5 mm	182.0	46.5
K- 07 25 05 01	G 1	1.5 - 20 bar	1.6	95.0	257.0 mm	201.0	56.0
K- 07 25 05 02	G 1 1/4	1.5 - 20 bar	4.2	104.0	385.0 mm	324.0	61.0
K- 07 25 05 03	G 1 1/2	1.5 - 20 bar	4.5	108.0	392.0 mm	331.0	61.0
K- 07 25 05 04	G 2	1.5 - 20 bar	7.2	146.5	419.0 mm	349.0	70.0