


K-DRG DRV 250 NIEDERDRUCK

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

DRV 250 pressure regulators, low-pressure type



Ieejas spiediens
Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series)
Temperatūras diapazons
Max. 75 °C
Samazināšanas process
Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series)
Blīvējums
NBR
Atsperes korpuss
Pressed brass up to DN 25, Grey cast iron from DN 32
Korpuss
Red brass 2.1096.01

Apraksts

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C mm	D mm
K- 07 25 04 94	G 1/4	0.2 - 2 bar	0.5	70.0	185.5 mm	140.0	45.5
K- 07 25 04 95	G 3/8	0.2 - 2 bar	0.6	70.0	185.5 mm	140.0	45.5
K- 07 25 04 96	G 1/2	0.2 - 2 bar	1.2	85.0	232.5 mm	186.0	46.5