

Pressure regulators with pressure supply at both ends



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the knob down. &lt;br&gt;By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmers
K- 07 25 00 31	G 1/4	0.1 - 3 bar	2000	47.8	94.8 mm	67.0	27.8	6	1
K- 07 25 00 32	G 1/4	0.2 - 6 bar	2000	47.8	94.8 mm	67.0	27.8	6	1
K- 07 25 00 30	G 1/4	0.5 - 10 bar	2000	47.8	94.8 mm	67.0	27.8	6	1
K- 07 25 00 34	G 1/2	0.1 - 3 bar	5500	68.8	134.1 mm	99.0	35.1	15	2
K- 07 25 00 35	G 1/2	0.2 - 6 bar	5500	68.8	134.1 mm	99.0	35.1	15	2
K- 07 25 00 33	G 1/2	0.5 - 10 bar	5500	68.8	134.1 mm	99.0	35.1	15	2