

Pressure regulators with pressure supply at both ends



Ieejas spiediens  
Max. 25 bar  
Vides temperatūra  
Max. 50 °C  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P1 = 10 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc  
Caurplūdes vērtības mērijums  
At P1 = 10 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the knob down. &lt;br&gt;By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 04 33	G 1/4	0.5 - 6 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 34	G 1/4	0.5 - 10 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 35	G 1/4	0.5 - 16 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 36	G 3/8	0.5 - 6 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 37	G 3/8	0.5 - 10 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 38	G 3/8	0.5 - 16 bar	1800	48.0	98.0 mm	26.0