

K-DRG FL RUECKSTERERBAR M MANO VA

Non-reversible, stainless steel pressure regulators for liquid media, stainless steel pressure gauge



Ieejas spiediens
Max. 30 bar (Control range 0.5 - 8.0 bar), Max. 50 bar (Control range 1.0 - 15.0 bar)
Vides temperatūra
Max. 80 °C
Vielas temperatūra
max. 80 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p \leq 1$ bar
Blīvējums
FKM
Materiāls
stainless steel 1.4404 (AISI 316L)
Membrāna
PTFE on NBR base
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p \leq 1$ bar

Apraksts

Stainless steel regulators containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm
K- 07 25 02 10	G 1/4	0.5 - 8.0 bar	200	65.0	162.0 mm	37.0	125.0
K- 07 25 02 11	G 1/4	1.0 - 15.0 bar	330	65.0	162.0 mm	37.0	125.0
K- 07 25 02 08	G 1/2	0.5 - 8.0 bar	660	80.0	164.0 mm	37.0	127.0
K- 07 25 02 09	G 1/2	1.0 - 15.0 bar	1800	80.0	164.0 mm	37.0	127.0