

# K-DRG FL RUECKSTERERBAR M MANO VA

Non-reversible, stainless steel pressure regulators for liquid media, stainless steel pressure gauge



Ieejas spiediens  
Max. 30 bar (Control range 0.5 - 8.0 bar), Max. 50 bar (Control range 1.0 - 15.0 bar)  
Vides temperatūra  
Max. 80 °C  
Vielas temperatūra  
max. 80 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p \leq 1$  bar  
Blīvējums  
FKM  
Materiāls  
stainless steel 1.4404 (AISI 316L)  
Membrāna  
PTFE on NBR base  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p \leq 1$  bar

## Apraksts

Stainless steel regulators containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm
K- 07 25 02 10	G 1/4	0.5 - 8.0 bar	200	65.0	162.0 mm	37.0	125.0
K- 07 25 02 11	G 1/4	1.0 - 15.0 bar	330	65.0	162.0 mm	37.0	125.0
K- 07 25 02 08	G 1/2	0.5 - 8.0 bar	660	80.0	164.0 mm	37.0	127.0
K- 07 25 02 09	G 1/2	1.0 - 15.0 bar	1800	80.0	164.0 mm	37.0	127.0