

K-DRG MEMBRAN O SEKUNDAERL MANO MS

Pressure regulators for Water with pressure gauge



Ieejas spiediens
Max. 40 bar
Temperatūras diapazons
+5 °C to +90 °C
Caurplūde
At P1 = 7 bar, P2 = 6 bar and $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Brass
Membrāna
NBR
Rokrāts
Plastic (G 1/4, G 1/2), rotary switch (G 3/4, G 1)
Caurplūdes vērtības mērijums
At P1 = 7 bar, P2 = 6 bar and $\Delta p = 1$ bar

Apraksts

Brass diaphragm pressure regulators with non-self-relieving design, specially for use with water. The regulator protects water installations against high system pressure, prevents pressure fluctuations and helps reduce water consumption. Undesirable flow noises are kept to a minimum.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm
K- 07 25 04 78	G 1/4	0.5 - 6 bar	3	45.0	104.0 mm	23.0	81.0
K- 07 25 04 79	G 1/4	0.5 - 10 bar	3	45.0	104.0 mm	23.0	81.0
K- 07 25 04 80	G 1/2	0.5 - 6 bar	15	72.0	153.0 mm	30.0	123.0
K- 07 25 04 81	G 1/2	0.5 - 10 bar	15	72.0	153.0 mm	30.0	123.0
K- 07 25 04 82	G 1	0.5 - 6 bar	24	114.0	216.0 mm	41.0	175.0
K- 07 25 04 83	G 1	0.5 - 10 bar	24	114.0	216.0 mm	41.0	175.0
K- 07 25 04 84	G 1 1/2	0.5 - 6 bar	56	114.0	233.0 mm	50.0	183.0
K- 07 25 04 85	G 1 1/2	0.5 - 10 bar	56	114.0	233.0 mm	50.0	183.0