



Ieejas spiediens
Max. 16 bar
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the button down.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 03	G 1/8	0.1 - 3 bar	1100	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 04	G 1/8	0.2 - 6 bar	1100	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 01	G 1/8	0.5 - 10 bar	1100	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 02	G 1/8	0.5 - 16 bar	1100	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 05	G 1/4	0.1 - 3 bar	1100	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 06	G 1/4	0.2 - 6 bar	1100	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 07	G 1/4	0.5 - 10 bar	1100	40.0	85.0 mm	63.0	22.0	5	0