

K-DRG PNEU FERNGEST MULTIFIX

Pressure regulators with pneumatic remote control



Ieejas spiediens
Max. 16 bar
Izejas spiediens
corresponds to the set pressure of the pilot pressure regulator
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Regulēšanas gaisa pieslēgums
G 1/8

Apraksts

Diaphragm pressure regulator, self-relieving, with pneumatic remote control. The pressure is set with a pilot pressure regulator (1:1 ratio). Either a standard or a precision pressure regulator can be used to regulate the pilot pressure.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Diagramma	Vītnes	Caurplūde nom. l/min	A mm	B	C mm	D mm
K- 07 25 19 56		G 1/4	1800	48.0	75.0 mm	48.0	27.0
K- 07 25 19 57		G 1/2	4800	69.0	94.0 mm	59.0	35.0
K- 07 25 19 58		G 1	12500	100.0	112.0 mm	60.0	52.0