

# K-DRG PNEU FERNGEST MULTIFIX

Pressure regulators with pneumatic remote control



Ieejas spiediens  
Max. 16 bar  
Izejas spiediens  
corresponds to the set pressure of the pilot pressure regulator  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc, Aluminium for G 1 variant  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Regulēšanas gaisa pieslēgums  
G 1/8

## Apraksts

Diaphragm pressure regulator, self-relieving, with pneumatic remote control. The pressure is set with a pilot pressure regulator (1:1 ratio). Either a standard or a precision pressure regulator can be used to regulate the pilot pressure.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Diagramma	Vītnes	Caurplūde nom. l/min	A mm	B	C mm	D mm
K- 07 25 19 56		G 1/4	1800	48.0	75.0 mm	48.0	27.0
K- 07 25 19 57		G 1/2	4800	69.0	94.0 mm	59.0	35.0
K- 07 25 19 58		G 1	12500	100.0	112.0 mm	60.0	52.0