

K-DRG SCHALTTAFELEINBAU STANDARD

Pressure regulators



Ieejas spiediens
Max. 16 bar K-07250359 - K-07250366), max. 25 bar (K-07250367 - K-07250378)
Vides temperatūra
Max. 80 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc, painted silver
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

- incl. panel nut and washer -, Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	C mm	D mm	DN	Sadales dēļa vitne
K- 07 25 03 59	G 1/4	0.5 - 3 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 60	G 1/4	0.5 - 6 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 61	G 1/4	0.5 - 10 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 62	G 1/4	0.5 - 16 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 63	G 3/8	0.5 - 3 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 64	G 3/8	0.5 - 6 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 65	G 3/8	0.5 - 10 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 66	G 3/8	0.5 - 16 bar	1000	54.0	32.0	97.5	6	M 20 x 1.5
K- 07 25 03 67	G 1/2	0.1 - 3 bar	2200	70.0	34.0	111.9	15	M 20 x 1.5
K- 07 25 03 68	G 1/2	0.5 - 6 bar	2200	70.0	34.0	111.9	15	M 20 x 1.5
K- 07 25 03 69	G 1/2	0.5 - 10 bar	2200	70.0	34.0	111.9	15	M 20 x 1.5
K- 07 25 03 70	G 1/2	0.5 - 16 bar	2200	70.0	34.0	111.9	15	M 20 x 1.5
K- 07 25 03 71	G 3/4	0.1 - 3 bar	5000	90.0	31.0	132.4	20	M 20 x 1.5
K- 07 25 03 72	G 3/4	0.5 - 6 bar	5000	90.0	31.0	132.4	20	M 20 x 1.5
K- 07 25 03 73	G 3/4	0.5 - 10 bar	5000	90.0	31.0	132.4	20	M 20 x 1.5
K- 07 25 03 74	G 3/4	0.5 - 16 bar	5000	90.0	31.0	132.4	20	M 20 x 1.5
K- 07 25 03 75	G 1	0.1 - 3 bar	5000	90.0	31.0	132.4	25	M 20 x 1.5
K- 07 25 03 76	G 1	0.5 - 6 bar	5000	90.0	31.0	132.4	25	M 20 x 1.5
K- 07 25 03 77	G 1	0.5 - 10 bar	5000	90.0	31.0	132.4	25	M 20 x 1.5
K- 07 25 03 78	G 1	0.5 - 16 bar	5000	90.0	31.0	132.4	25	M 20 x 1.5