



Ieejas spiediens  
Max. 28 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR/TPU  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc, painted silver  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Reversible diaphragm pressure regulators with self-relieving design in compact design. The pressure setting can be locked by pushing the knob down.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm	D mm	DN
K- 07 25 03 22	G 1/8	0.15 - 3.5 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 23	G 1/8	0.2 - 7.0 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 24	G 1/8	0.5 - 10.0 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 25	G 1/4	0.15 - 3.5 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 26	G 1/4	0.2 - 7.0 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 27	G 1/4	0.5 - 10.0 bar	340	43.0	72.5 mm	9.5	63.0	5