


Pressure regulators for drinking water (without DVGW appr.), high outlet pressure (max. 12 bar)



Ieejas spiediens  
 Max. 16 bar (low-pressure type), Max. 25 bar (high-pressure type)  
 Veidlapa  
 Min. 1.2 bar (low-pressure type), Max. 2.5 bar (high-pressure type)  
 min. spiediena kritums  
 1 bar  
 Eksploatācijas temperatūra  
 Max. 75 °C  
 Blīvējums  
 NBR-SBR  
 Atsperes korpuss  
 Plastic PA 6 (up to DN 32, low-pressure type), Hot-pressed brass (up to DN 32, high-pressure type), Cast iron (from DN 40)  
 Iekšējās daļas  
 Plastic, brass, stainless steel  
 Korpuss  
 Bronze (Rg5)

## Apraksts

Pressure regulator with pressure-reduced single-seated piston valve or single-seated diaphragm valve and built-in strainer. Specially designed for use with water. &lt;br&gt;The device is also suitable for all other applications involving neutral non-sticky liquids, air and neutral non-flammable gases.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	min. spiediena kritums bar	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m <sup>3</sup> /h	A mm	B	C mm	D mm	DN
K- 07 25 04 45	1	R 1/2	1.5 - 12 bar	2.9	137.0	177.0 mm	150.0	27.0	15
K- 07 25 04 46	1	R 3/4	1.5 - 12 bar	3.9	141.0	177.0 mm	150.0	27.0	20
K- 07 25 04 47	1	R 1	1.5 - 12 bar	5.4	160.0	178.5 mm	150.0	28.5	25
K- 07 25 04 48	1	R 1 1/4	1.5 - 12 bar	6.1	177.2	234.0 mm	187.0	47.0	32
K- 07 25 04 49	1	R 1 1/2	1.5 - 12 bar	12.0	210.0	379.0 mm	320.0	59.0	40
K- 07 25 04 50	1	R 2	1.5 - 12 bar	13.0	210.0	381.0 mm	320.0	61.0	50