



Ieejas spiediens
Max. 25 bar
Vides temperatūra
Max. 50 °C
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Atsperes korpuss
POM
Korpuss
Die-cast zinc
Membrāna
NBR
Caurplūdes vērtības mērijums
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the knob down. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 04 18	G 1/4	0.5 - 6 bar	2000	48.0	98.0 mm	26.0
K- 07 25 04 19	G 1/4	0.5 - 10 bar	2000	48.0	98.0 mm	26.0
K- 07 25 04 20	G 1/4	0.5 - 16 bar	2000	48.0	98.0 mm	26.0
K- 07 25 04 21	G 3/8	0.5 - 6 bar	3200	48.0	98.0 mm	26.0
K- 07 25 04 22	G 3/8	0.5 - 10 bar	3200	48.0	98.0 mm	26.0
K- 07 25 04 23	G 3/8	0.5 - 16 bar	3200	48.0	98.0 mm	26.0
K- 07 25 04 24	G 1/2	0.5 - 6 bar	7000	70.0	134.0 mm	32.5
K- 07 25 04 25	G 1/2	0.5 - 10 bar	7000	70.0	134.0 mm	32.5
K- 07 25 04 26	G 1/2	0.5 - 16 bar	7000	70.0	134.0 mm	32.5
K- 07 25 04 27	G 3/4	0.5 - 6 bar	8000	70.0	134.0 mm	32.5
K- 07 25 04 28	G 3/4	0.5 - 10 bar	8000	70.0	134.0 mm	32.5
K- 07 25 04 29	G 3/4	0.5 - 16 bar	8000	70.0	134.0 mm	32.5
K- 07 25 04 30	G 1	0.5 - 6 bar	8000	124.0	134.0 mm	32.5
K- 07 25 04 31	G 1	0.5 - 10 bar	8000	124.0	134.0 mm	32.5
K- 07 25 04 32	G 1	0.5 - 16 bar	8000	124.0	134.0 mm	32.5