

# K-DRG VORDRUCK STANDARD-MINI

Pressure regulators



Ieejas spiediens  
Max. 25 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc, painted silver  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the knob down.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm	D mm	DN
K- 07 25 03 28	G 1/8	0.1 - 3 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 29	G 1/8	0.5 - 6 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 30	G 1/8	0.5 - 10 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 31	G 1/8	0.5 - 16 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 32	G 1/4	0.1 - 3 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 33	G 1/4	0.5 - 6 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 34	G 1/4	0.5 - 10 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 35	G 1/4	0.5 - 16 bar	330	40.0	76.3 mm	15.0	61.3	5