

K-DRG VORDRUCK STANDARD-MINI

Pressure regulators



Ieejas spiediens
Max. 25 bar
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, painted silver
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the knob down.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN
K- 07 25 03 28	G 1/8	0.1 - 3 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 29	G 1/8	0.5 - 6 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 30	G 1/8	0.5 - 10 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 31	G 1/8	0.5 - 16 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 32	G 1/4	0.1 - 3 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 33	G 1/4	0.5 - 6 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 34	G 1/4	0.5 - 10 bar	330	40.0	76.3 mm	15.0	61.3	5
K- 07 25 03 35	G 1/4	0.5 - 16 bar	330	40.0	76.3 mm	15.0	61.3	5