

K-DRG WASSER NIEDRIGER HINTERDRUCK

Pressure regulators for water, low outlet pressure (max. 2 bar)



Ieejas spiediens

Max. 16 bar (low-pressure type), Max. 25 bar (high-pressure type)

Veidlapa

Min. 1.2 bar (low-pressure type), Max. 2.5 bar (high-pressure type)

min. spiediena kritums

1 bar

Ekspluatācijas temperatūra

Max. 75 °C

Blīvējums

NBR-SBR

Atsperes korpus

Plastic PA 6 (up to DN 32, low-pressure type), Hot-pressed brass (up to DN 32, high-pressure type), Cast iron (from DN 40)

Iekšējās daļas

Plastic, brass, stainless steel

Korpuss

Bronze (Rg5)

Apraksts

Pressure regulator with pressure-reduced single-seated piston valve or single-seated diaphragm valve and built-in strainer. Specially designed for use with water. The device is also suitable for all other applications involving neutral non-sticky liquids, air and neutral non-flammable gases.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	min. spiediena kritums bar	Vitnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C mm	D mm	DN
K- 07 25 04 51	1	R 1/2	0.2 - 2 bar	2.9	137.0	154.0 mm	127.0	27.0	15
K- 07 25 04 52	1	R 3/4	0.2 - 2 bar	3.9	141.0	154.0 mm	127.0	27.0	20
K- 07 25 04 53	1	R 1	0.2 - 2 bar	5.4	160.6	154.0 mm	126.0	28.5	25
K- 07 25 04 54	1	R 1 1/4	0.2 - 2 bar	6.1	177.2	156.0 mm	109.0	47.0	32
K- 07 25 04 55	1	R 1 1/2	0.2 - 2 bar	12.0	210.0	359.0 mm	300.0	59.0	40
K- 07 25 04 56	1	R 2	0.2 - 2 bar	13.0	210.0	361.0 mm	300.0	61.0	50