



Ieejas spiediens  
Max. 40 bar  
Vides temperatūra  
Max. 90 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
2500 l/min  
Blīvējums  
NBR  
Korpuss  
Aluminium  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the button down. We recommend always using these controllers in conjunction with our K-07250615 and K-07250615 filters.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	DN
K- 07 25 08 11	G 1 1/2	0.5 - 6 bar	180.0	246.0 mm	50
K- 07 25 08 12	G 1 1/2	0.5 - 10 bar	180.0	246.0 mm	50
K- 07 25 08 13	G 1 1/2	0.5 - 16 bar	180.0	246.0 mm	50
K- 07 25 08 14	G 1 1/2	0.5 - 25 bar	180.0	246.0 mm	50
K- 07 25 08 15	G 2	0.5 - 6 bar	160.0	246.0 mm	50
K- 07 25 08 16	G 2	0.5 - 10 bar	160.0	246.0 mm	50
K- 07 25 08 17	G 2	0.5 - 16 bar	160.0	246.0 mm	50
K- 07 25 08 18	G 2	0.5 - 25 bar	160.0	246.0 mm	50