



Ieejas spiediens  
Max. 25 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
50000 l/min  
Blīvējums  
NBR  
Korpuss  
Aluminium, painted silver  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design for very high flow rates. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the knob down. We recommend always using these controllers in conjunction with our K-07250607 and K-07250609 filters.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	DN
K- 07 25 08 03	G 1 1/2	0.1 - 3 bar	188.0	261.0 mm	50
K- 07 25 08 04	G 1 1/2	0.2 - 6 bar	188.0	261.0 mm	50
K- 07 25 08 05	G 1 1/2	0.5 - 10 bar	188.0	261.0 mm	50
K- 07 25 08 06	G 1 1/2	0.5 - 16 bar	188.0	261.0 mm	50
K- 07 25 08 07	G 2	0.1 - 3 bar	160.0	261.0 mm	50
K- 07 25 08 08	G 2	0.2 - 6 bar	160.0	261.0 mm	50
K- 07 25 08 09	G 2	0.5 - 10 bar	160.0	261.0 mm	50
K- 07 25 08 10	G 2	0.5 - 16 bar	160.0	261.0 mm	50