

K-KONSTANT DRUCKREGLER STANDARD 1

Constant-pressure regulators



Ieejas spiediens
Max. 25 bar (G 1/4 to G 1/2), Max. 40 bar (G 3/4 to G 1 1/2)
Vides temperatūra
Max. 90 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc for (G 1/4 to G 1/2), for Brass (G 3/4 to G 1 1/2)
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure regulators maintain a constant working pressure regardless of variations in the inlet pressure.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm	D mm	DN
K- 07 25 03 82	G 1/4	0.5 - 3 bar	3000	77.0	165.0 mm	33.0	132.0	10
K- 07 25 03 83	G 1/4	0.5 - 6 bar	2500	77.0	165.0 mm	33.0	132.0	10
K- 07 25 03 84	G 1/4	0.5 - 10 bar	2000	77.0	165.0 mm	33.0	132.0	10
K- 07 25 03 85	G 1/4	0.5 - 16 bar	1600	77.0	165.0 mm	33.0	132.0	10
K- 07 25 03 86	G 3/8	0.5 - 3 bar	3000	70.0	165.0 mm	33.0	132.0	10
K- 07 25 03 87	G 3/8	0.5 - 6 bar	2500	70.0	165.0 mm	33.0	132.0	10
K- 07 25 03 88	G 3/8	0.5 - 10 bar	2000	70.0	165.0 mm	33.0	132.0	10
K- 07 25 03 89	G 3/8	0.5 - 16 bar	1600	70.0	165.0 mm	33.0	132.0	10
K- 07 25 03 90	G 3/8	0.5 - 3 bar	3500	90.0	170.0 mm	32.0	138.0	15
K- 07 25 03 91	G 3/8	0.5 - 6 bar	3000	90.0	170.0 mm	32.0	138.0	15
K- 07 25 03 92	G 3/8	0.5 - 10 bar	2670	90.0	170.0 mm	32.0	138.0	15
K- 07 25 03 93	G 3/8	0.5 - 16 bar	2000	90.0	170.0 mm	32.0	138.0	15
K- 07 25 03 94	G 1/2	0.5 - 3 bar	3500	82.0	170.0 mm	32.0	138.0	15
K- 07 25 03 95	G 1/2	0.5 - 6 bar	3000	82.0	170.0 mm	32.0	138.0	15
K- 07 25 03 96	G 1/2	0.5 - 10 bar	2670	82.0	170.0 mm	32.0	138.0	15
K- 07 25 03 97	G 1/2	0.5 - 16 bar	2000	82.0	170.0 mm	32.0	138.0	15