

Precision pressure regulators with continuous pressure supply



Ieejas spiediens  
 Max. 16 bar  
 Temperatūras diapazons  
 -10 °C to +50 °C  
 Darba vides  
 Saspiests gaiss  
 Caurplūde  
 At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar  
 Korpusa  
 Material: Grivory® (PA 66)  
 Membrāna  
 NBR  
 Pieslēguma vītne  
 Material: Die-cast zinc  
 Iekšējā gaisa patēriņš  
 2.6 l/min at P2 = 6 bar (depending on secondary pressure)  
 Caurplūdes vērtības mērījums  
 At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Precision diaphragm pressure regulators with self-relieving design and excellent flow rates in modern design for mounting side by side. &lt;br&gt;By assembling two or more controllers together, it is possible to supply several working air circuits with different pressures via a single supply line.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm
K- 07 25 09 66	G 1/4	0.1 - 1 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 67	G 1/4	0.1 - 2 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 68	G 1/4	0.2 - 4 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 69	G 1/4	0.5 - 8 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 70	G 1/4	0.5 - 10 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 71	G 3/8	0.1 - 1 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 72	G 3/8	0.1 - 2 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 73	G 3/8	0.2 - 4 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 74	G 3/8	0.5 - 8 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 75	G 3/8	0.5 - 10 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 76	G 3/8	0.1 - 1 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 77	G 3/8	0.1 - 2 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 78	G 3/8	0.2 - 4 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 79	G 3/8	0.5 - 8 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 80	G 3/8	0.5 - 10 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 81	G 1/2	0.1 - 1 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 82	G 1/2	0.1 - 2 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 83	G 1/2	0.2 - 4 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 84	G 1/2	0.5 - 8 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 85	G 1/2	0.5 - 10 bar	5000	63.0	149.5 mm	110.0