

# K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
Max. 80 °C  
Vielas temperatūra  
max. 80 °C  
Darba vides  
Fine-filtered (5 µm), unlubricated compressed air, neutral gases  
Manometra pieslēgums  
G 1/4  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc  
Vārsta konuss, membrāna  
FPM

## Apraksts

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm
K- 07 25 09 39	G 1/4	0 - 1 bar	600	82.0	148.0 mm	19.5	128.5
K- 07 25 09 40	G 1/4	0.1 - 3 bar	760	82.0	148.0 mm	19.5	128.5
K- 07 25 09 41	G 1/4	0.2 - 6 bar	550	82.0	148.0 mm	19.5	128.5
K- 07 25 09 42	G 1/4	0.5 - 10 bar	400	82.0	148.0 mm	19.5	128.5