

K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption



Ieejas spiediens
Max. 16 bar
Vides temperatūra
Max. 80 °C
Vielas temperatūra
max. 80 °C
Darba vides
Fine-filtered (5 µm), unlubricated compressed air, neutral gases
Manometra pieslēgums
G 1/4
Blīvējums
NBR
Korpuss
Die-cast zinc
Vārsta konuss, membrāna
FPM

Apraksts

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm
K- 07 25 09 39	G 1/4	0 - 1 bar	600	82.0	148.0 mm	19.5	128.5
K- 07 25 09 40	G 1/4	0.1 - 3 bar	760	82.0	148.0 mm	19.5	128.5
K- 07 25 09 41	G 1/4	0.2 - 6 bar	550	82.0	148.0 mm	19.5	128.5
K- 07 25 09 42	G 1/4	0.5 - 10 bar	400	82.0	148.0 mm	19.5	128.5