

# K-NEBELOEL PC-BEHAEI SCHUTZK HANSA

Oil-mist lubricators



Ieejas spiediens  
0.5 - 16 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P2 = 6 bar, pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Aizsarggrozs  
Polyamide  
Korpuss  
Material: Grivory® (PA 66)  
Pieslēguma vītne  
Material: Die-cast zinc  
Pilienu aizsargs  
PA  
Tvertne  
Polycarbonate (with bayonet lock)  
Eļļas veids  
CL 32 acc. to DIN 51517 - ISO VG 32  
Caurplūdes vērtības mērijums  
At P2 = 6 bar, pressure drop  $\Delta p = 1$  bar

## Apraksts

Oil-mist lubricators with excellent flow rates in modern design. These devices can be used to top up oil automatically. A hose must be connected to the threaded nipple on the oil bowl for this purpose. When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 08 79	G 1/4	2800	52.0	183.0 mm	62.2
K- 07 25 08 80	G 3/8	2800	52.0	183.0 mm	62.2
K- 07 25 08 81	G 3/8	8000	63.0	208.2 mm	69.7
K- 07 25 08 82	G 1/2	8000	63.0	208.2 mm	69.7
K- 07 25 08 77	G 3/4	16000	85.0	270.4 mm	87.9
K- 07 25 08 78	G 1	16000	85.0	270.4 mm	87.9