

# K-NEBELOELER METALLBEHAE T STANDARD

Oil-mist lubricators with metal bowl and metal sight dome



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc, painted silver  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Eļļas veids  
CL 32 acc. to DIN 51517 - ISO VG 32  
Caurplūdes vērtības mērijums  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Proportional lubricators, oil can be filled under pressure.

## Produkts

| Apzīmējums     | Vītnes  | Caurplūde nom.<br>l/min | A<br>mm | C<br>mm | D<br>mm | DN |
|----------------|---------|-------------------------|---------|---------|---------|----|
| K- 07 25 08 88 | G 1/4   | 1200                    | 50.0    | 51.0    | 119.5   | 6  |
| K- 07 25 08 91 | G 3/8   | 1200                    | 50.0    | 51.0    | 119.5   | 6  |
| K- 07 25 08 94 | G 3/8   | 2400                    | 70.0    | 51.0    | 145.0   | 10 |
| K- 07 25 08 97 | G 1/2   | 4000                    | 79.0    | 55.0    | 157.0   | 15 |
| K- 07 25 09 00 | G 3/4   | 9000                    | 102.0   | 58.0    | 160.0   | 20 |
| K- 07 25 09 03 | G 1     | 9000                    | 90.0    | 58.0    | 160.0   | 25 |
| K- 07 25 09 06 | G 1 1/4 | 9000                    | 137.0   | 70.0    | 232.0   | 40 |
| K- 07 25 09 09 | G 1 1/2 | 9000                    | 125.0   | 70.0    | 232.0   | 45 |