

# K-NEBELOELER PC-BEHAEEL S STANDARD

Oil-mist lubricators with polycarbonate bowl and bowl guard



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc, painted silver  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Eļļas veids  
CL 32 acc. to DIN 51517 - ISO VG 32  
Caurplūdes vērtības mērijums  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Proportional lubricators, oil can be filled under pressure.

## Produkts

Apzīmējums	Vītnes	Caurplūde nom. l/min	A mm	C mm	D mm	DN
K- 07 25 08 89	G 1/4	1200	50.0	51.0	118.0	6
K- 07 25 08 92	G 3/8	1200	50.0	51.0	118.0	6
K- 07 25 08 95	G 3/8	2400	70.0	51.0	129.5	10
K- 07 25 08 98	G 1/2	4000	79.0	55.0	157.0	15
K- 07 25 09 01	G 3/4	9000	102.0	58.0	160.0	20
K- 07 25 09 04	G 1	9000	90.0	58.0	160.0	25
K- 07 25 09 07	G 1 1/4	9000	137.0	70.0	232.0	40
K- 07 25 09 10	G 1 1/2	9000	125.0	70.0	232.0	45