

K-NEBELOELER PC-BEHAEL S STANDARD

Oil-mist lubricators with polycarbonate bowl and bowl guard



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Eļļas veids
CL 32 acc. to DIN 51517 - ISO VG 32
Caurplūdes vērtības mērijums
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Proportional lubricators, oil can be filled under pressure.

Produkts

| Apzīmējums | Vītnes | Caurplūde nom. l/min | A mm | C mm | D mm | DN |
|----------------|---------|-------------------------|---------|---------|---------|----|
| K- 07 25 08 89 | G 1/4 | 1200 | 50.0 | 51.0 | 118.0 | 6 |
| K- 07 25 08 92 | G 3/8 | 1200 | 50.0 | 51.0 | 118.0 | 6 |
| K- 07 25 08 95 | G 3/8 | 2400 | 70.0 | 51.0 | 129.5 | 10 |
| K- 07 25 08 98 | G 1/2 | 4000 | 79.0 | 55.0 | 157.0 | 15 |
| K- 07 25 09 01 | G 3/4 | 9000 | 102.0 | 58.0 | 160.0 | 20 |
| K- 07 25 09 04 | G 1 | 9000 | 90.0 | 58.0 | 160.0 | 25 |
| K- 07 25 09 07 | G 1 1/4 | 9000 | 137.0 | 70.0 | 232.0 | 40 |
| K- 07 25 09 10 | G 1 1/2 | 9000 | 125.0 | 70.0 | 232.0 | 45 |