

K-NEBELOELER PC-BEHAELTER MULTIFIX

Oil-mist lubricators with polycarbonate bowl



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Manual
Eļļas veids
CL 32 acc. to DIN 51517 - ISO VG 32
Caurplūdes vērtības mērījums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Proportional lubricators, oil can be filled under pressure.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 91	G 1/4	1900	47.8	167.8 mm	58.0	109.8	6	1
K- 07 25 00 94	G 3/8	1900	47.8	167.8 mm	58.0	109.8	10	1
K- 07 25 00 97	G 1/2	5000	68.8	198.2 mm	66.1	132.1	15	2
K- 07 25 01 00	G 3/4	5000	68.8	198.2 mm	66.1	132.1	20	2
K- 07 25 01 03	G 1	18000	100.0	324.3 mm	82.7	241.6	25	3