

K-NEBELOELER PC-BEHAEALTER VARIOBLOC

Oil-mist lubricators with polycarbonate bowl



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc
Pilienu aizsargs
PA
Eļļas veids
CL 32 acc. to DIN 51517 - ISO VG 32
Caurplūdes vērtības mērijums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm |
|----------------|--------|-------------------------|---------|----------|---------|
| K- 07 25 09 13 | G 1/4 | 3400 | 48.0 | 171.0 mm | 52.0 |
| K- 07 25 09 15 | G 3/8 | 4400 | 48.0 | 171.0 mm | 52.0 |
| K- 07 25 09 17 | G 1/2 | 4600 | 70.0 | 224.0 mm | 57.0 |
| K- 07 25 09 19 | G 3/4 | 7500 | 70.0 | 224.0 mm | 57.0 |
| K- 07 25 09 21 | G 1 | 7500 | 124.0 | 224.0 mm | 57.0 |