

# K-NEBELOELER PC-BEHAELTER

## VARIOBLOC

Oil-mist lubricators with polycarbonate bowl



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc  
Pilienu aizsargs  
PA  
Eļļas veids  
CL 32 acc. to DIN 51517 - ISO VG 32  
Caurplūdes vērtības mērijums  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 09 13	G 1/4	3400	48.0	171.0 mm	52.0
K- 07 25 09 15	G 3/8	4400	48.0	171.0 mm	52.0
K- 07 25 09 17	G 1/2	4600	70.0	224.0 mm	57.0
K- 07 25 09 19	G 3/4	7500	70.0	224.0 mm	57.0
K- 07 25 09 21	G 1	7500	124.0	224.0 mm	57.0