



Ieejas spiediens  
Min. 2 bar, max. 16 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc, Aluminium for G 3/4 and G 1 variant  
Caurplūdes vērtības mērijums  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	Caurpl_de nom. l/min	A mm	B	D mm
K- 07 25 11 54	G 1/4	1000	47.8	54.2 mm	26.8
K- 07 25 11 55	G 1/2	4000	68.8	71.6 mm	35.1
K- 07 25 19 34	G 3/4	12000	99.7	104.0 mm	52.0
K- 07 25 19 35	G 1	12000	99.7	104.0 mm	52.0