



Ekspluatācijas spiediens  
2 - 25 bar  
Caurplūde  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Caurplūdes vērtības mērījums  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

For slow pressure build-up in pneumatic systems, e.g. after an emergency stop. The valve opens to full flow at approximately 60% of the set operating pressure. <br>The filling time can be set by turning the adjusting screw. Used in combination with multi-piece service units.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | Caurpl_de nom.<br>l/min | A<br>mm | B       | Ekspluatācijas spiediens bar |
|----------------|--------|-------------------------|---------|---------|------------------------------|
| K- 07 25 11 84 | G 1/4  | 1200                    | 48.0    | 54.0 mm | 2 - 25 bar                   |
| K- 07 25 11 85 | G 3/8  | 1400                    | 48.0    | 54.0 mm | 2 - 25 bar                   |
| K- 07 25 11 86 | G 1/2  | 3800                    | 70.0    | 72.0 mm | 2 - 25 bar                   |
| K- 07 25 11 87 | G 3/4  | 4200                    | 70.0    | 72.0 mm | 2 - 25 bar                   |
| K- 07 25 11 88 | G 1    | 4200                    | 124.0   | 72.0 mm | 2 - 25 bar                   |