

K-WTEH 2-TLG MET M ABLV TRO STANDAD

Service units with metal bowl and manual drain valve, metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Regulēšanas diapazons
0.5 to 10 bar (polycarbonate bowl / bowl guard) 0.5 to 16 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (Size 1 / Size 3), 40 μm (Size 2 / Size 4)
Korpuss
Die-cast zinc / Aluminium, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm | DN | Ø manometram |
|----------------|--------|-------------------------|---------|----------|---------|----|--------------|
| K- 07 25 14 94 | G 1/4 | 600 | 117.0 | 240.0 mm | 106.5 | 6 | 50 |
| K- 07 25 14 97 | G 3/8 | 600 | 117.0 | 240.0 mm | 106.5 | 6 | 50 |
| K- 07 25 15 00 | G 3/8 | 800 | 150.0 | 281.5 mm | 120.5 | 10 | 63 |
| K- 07 25 15 03 | G 1/2 | 2100 | 175.0 | 302.0 mm | 130.0 | 15 | 63 |
| K- 07 25 15 06 | G 3/4 | 4000 | 220.0 | 454.6 mm | 190.6 | 20 | 63 |
| K- 07 25 15 09 | G 1 | 4000 | 220.0 | 454.6 mm | 190.6 | 25 | 63 |