

K-WTEH 2-TLG MET SICH TROPF MULTIFI

Service units, 2-piece with metal bowl and sight glass, metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (BG 1 / BG 2), 40 μm (BG 3)
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Semi-automatic
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Regulēšanas diapazons | Caurpl_de nom. l/min | A mm | B | C mm | D mm | DN | Tipizmers |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|---------|----|-----------|
| K- 07 25 01 30 | G 1/4 | 0.5 - 10 bar | 1100 | 93.0 | 196.0 mm | 67.0 | 129.0 | 6 | 1 |
| K- 07 25 01 33 | G 3/8 | 0.5 - 10 bar | 1100 | 93.0 | 196.0 mm | 67.0 | 129.0 | 10 | 1 |
| K- 07 25 01 36 | G 1/2 | 0.5 - 10 bar | 3500 | 136.0 | 248,0 mm | 97.0 | 151.0 | 15 | 2 |
| K- 07 25 01 39 | G 3/4 | 0.5 - 10 bar | 3500 | 136.0 | 248,0 mm | 97.0 | 151.0 | 20 | 2 |
| K- 07 25 01 42 | G 1 | 0.5 - 10 bar | 10500 | 200.0 | 385.0 mm | 128.0 | 257.0 | 25 | 3 |