

K-WTEH 2-TLG PC MULTIFIX MINI

Service units, 2-piece with polycarbonate bowl



Ieejas spiediens
Max. 12 bar (also for metal tank!)

Vides temperatūra
Max. 60 °C

Vielas temperatūra
max. 60 °C

Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Blīvējums
NBR

Poru attālums filtra elementā
5 μm

Atsperes korpuss
POM-brass

Korpuss
Die-cast zinc

Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)

Drain valve
Semi-automatic

Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two or three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl. de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 01 25	G 1/8	0.5 - 10 bar	700	80.0	165.5 mm	63.0	102.5	5	0
K- 07 25 01 27	G 1/4	0.5 - 10 bar	700	80.0	165.5 mm	63.0	102.5	5	0