

# K-WTEH 2-TLG PC SCHU WAND

## V G

Service units, 2-piece with polycarbonate bowl, bowl guard and joiner for wall mounting, fully-automatic drain valve



Ieejas spiediens  
Max. 10 bar  
Vides temperatūra  
Max. 70 °C  
Vielas temperatūra  
max. 70 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$   
Atsperes korpuss  
POM  
Korpuss  
Die-cast aluminium  
Pilienu aizsargs  
Brass/POM  
Drain valve  
Semi- or fully-automatic  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Produkts

| Apzīmējums     | Vitnes | Regulēšanas diapazons | Caurpl_de nom.<br>l/min | A<br>mm | B        | C<br>mm | D<br>mm | Tipizmērs |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|---------|-----------|
| K- 07 25 13 96 | G 1/4  | 1.5 - 9 bar           | 1050                    | 115.0   | 225.5 mm | 82.5    | 143.0   | 300       |
| K- 07 25 13 98 | G 3/8  | 1.5 - 9 bar           | 1350                    | 115.0   | 225.5 mm | 82.5    | 143.0   | 300       |
| K- 07 25 14 00 | G 1/2  | 1.5 - 9 bar           | 1350                    | 115.0   | 225.5 mm | 82.5    | 143.0   | 300       |
| K- 07 25 14 02 | G 3/8  | 1.5 - 9 bar           | 3100                    | 152.0   | 270.5 mm | 104.0   | 166.5   | 400       |
| K- 07 25 14 04 | G 1/2  | 1.5 - 9 bar           | 3100                    | 152.0   | 270.5 mm | 104.0   | 166.5   | 400       |