

K-WTEH 3-TLG MET SICH TROPF MULTIFI

Service units, 3-piece with metal bowl and sight glass, metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (BG 1 / BG 2), 40 μm (BG 3)
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Semi-automatic
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmers
K- 07 25 01 11	G 1/4	0.5 - 10 bar	1100	138.0	196.0 mm	67.0	129.0	6	1
K- 07 25 01 14	G 3/8	0.5 - 10 bar	1100	138.0	196.0 mm	67.0	129.0	10	1
K- 07 25 01 17	G 1/2	0.5 - 10 bar	3000	202.0	248,0 mm	97.0	151.0	15	2
K- 07 25 01 20	G 3/4	0.5 - 10 bar	3000	202.0	248,0 mm	97.0	151.0	20	2
K- 07 25 01 23	G 1	0.5 - 10 bar	11300	300.0	385.0 mm	128.0	257.0	25	3