

K-WTEH 3-TLG MET SICH TROPF VARIOBL

Service units, 3-piece with metal bowl, incl. sight glass and metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
40 μ m
Atsperes korpuss
POM
Korpuss
Die-cast zinc
Membrāna
NBR
Pilienu aizsargs
PA
Drain valve
Manual
Caurplūdes vērtības mērijums
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 14 12	G 1/4	0.5 - 10 bar	1500	144.0	201,0 mm	68.0
K- 07 25 14 14	G 3/8	0.5 - 10 bar	1800	144.0	201,0 mm	68.0
K- 07 25 14 16	G 1/2	0.5 - 10 bar	3400	210.0	274.0 mm	98.0
K- 07 25 14 18	G 3/4	0.5 - 10 bar	5000	210.0	274.0 mm	98.0
K- 07 25 14 20	G 1	0.5 - 10 bar	5000	264.0	274.0 mm	98.0