

# K-WTEH 3-TLG PC H ABLV STANDARD

Service units with polycarbonate bowl and semi-automatic drain valve



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)  
Regulēšanas diapazons  
0.5 to 10 bar (polycarbonate bowl / bowl guard) 0.5 to 16 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$  (G 1/4 / G 3/8 / G 1/2), 40  $\mu\text{m}$  (G 3/8 / G 3/4 / G 1 / G 1 1/4 / G 1 1/2)  
Korpuss  
Die-cast zinc / Aluminium, painted silver  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

## Produkts

| Apzīmējums     | Vītnes  | Caurplūde nom.<br>l/min | A<br>mm | B        | C<br>mm | DN | Ø manometram |
|----------------|---------|-------------------------|---------|----------|---------|----|--------------|
| K- 07 25 14 49 | G 1/4   | 600                     | 172.0   | 182.6 mm | 51.0    | 6  | 50           |
| K- 07 25 14 56 | G 3/8   | 600                     | 185.0   | 182.6 mm | 51.0    | 6  | 50           |
| K- 07 25 14 59 | G 3/8   | 1400                    | 232.0   | 196.7 mm | 51.0    | 6  | 50           |
| K- 07 25 14 62 | G 1/2   | 3200                    | 259.0   | 223.4 mm | 55.0    | 15 | 63           |
| K- 07 25 14 65 | G 3/4   | 3200                    | 302.0   | 227.9 mm | 58.0    | 20 | 63           |
| K- 07 25 14 68 | G 1     | 3200                    | 302.0   | 227.9 mm | 58.0    | 25 | 63           |
| K- 07 25 14 71 | G 1 1/4 | 5000                    | 395.0   | 313.4 mm | 70.0    | 25 | 63           |
| K- 07 25 14 74 | G 1 1/2 | 5000                    | 395.0   | 313.4 mm | 70.0    | 35 | 63           |