

K-WTEH 3-TLG PC H ABLV STANDARD

Service units with polycarbonate bowl and semi-automatic drain valve



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Regulēšanas diapazons
0.5 to 10 bar (polycarbonate bowl / bowl guard) 0.5 to 16 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (G 1/4 / G 3/8 / G 1/2), 40 μm (G 3/8 / G 3/4 / G 1 / G 1 1/4 / G 1 1/2)
Korpuss
Die-cast zinc / Aluminium, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Produkts

Apzīmējums	Vītnes	Caurplūde nom. l/min	A mm	B	C mm	DN	Ø manometram
K- 07 25 14 49	G 1/4	600	172.0	182.6 mm	51.0	6	50
K- 07 25 14 56	G 3/8	600	185.0	182.6 mm	51.0	6	50
K- 07 25 14 59	G 3/8	1400	232.0	196.7 mm	51.0	6	50
K- 07 25 14 62	G 1/2	3200	259.0	223.4 mm	55.0	15	63
K- 07 25 14 65	G 3/4	3200	302.0	227.9 mm	58.0	20	63
K- 07 25 14 68	G 1	3200	302.0	227.9 mm	58.0	25	63
K- 07 25 14 71	G 1 1/4	5000	395.0	313.4 mm	70.0	25	63
K- 07 25 14 74	G 1 1/2	5000	395.0	313.4 mm	70.0	35	63