

K-WTEH 3-TLG PC MONO STANDARD-MINI

Service units, 3-piece with polycarbonate bowl and pressure gauge



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
350 l/min (2-piece), 300 l/min (3-piece)
Blīvējums
NBR
Poru attālums filtra elementā
5 µm
Korpuss
Die-cast zinc, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Compact, two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Regulēšanas diapazons | A mm | B | C mm | D mm | DN |
|----------------|--------|-----------------------|---------|----------|---------|---------|----|
| K- 07 25 14 52 | G 1/8 | 0.5 - 10 bar | 130.0 | 151.5 mm | 49.5 | 102.0 | 5 |
| K- 07 25 14 54 | G 1/4 | 0.5 - 10 bar | 130.0 | 151.5 mm | 49.5 | 102.0 | 5 |