

# K-WTEH 3-TLG PC SCHU

## VARIOBLOC

Service units, 3-piece with polycarbonate bowl and bowl guard



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P1 = 10 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
40  $\mu\text{m}$   
Atsperes korpuss  
POM  
Korpuss  
Die-cast zinc  
Membrāna  
NBR  
Pilienu aizsargs  
PA  
Drain valve  
Manual  
Caurplūdes vērtības mērijums  
At P1 = 10 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 22 86	G 1/4	0.5 - 10 bar	1500	144.0	201,0 mm	68.0
K- 07 25 22 85	G 3/8	0.5 - 10 bar	1800	144.0	201,0 mm	68.0
K- 07 25 22 84	G 1/2	0.5 - 10 bar	3400	210.0	247,0 mm	98.0
K- 07 25 22 83	G 3/4	0.5 - 10 bar	5000	210.0	247,0 mm	98.0
K- 07 25 22 82	G 1	0.5 - 10 bar	5000	264.0	247,0 mm	98.0