

K-WTEH 3-TLG PC-BEHAEL SCHUTZK MULT

Service units, 3-piece with polycarbonate bowl and bowl guard



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (BG 1 / BG 2), 40 μm (BG 3)
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Semi-automatic
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Regulēšanas diapazons | Caurpl_de nom. l/min | A mm | B | C mm | D mm | DN | Tipizmers |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|---------|----|-----------|
| K- 07 25 01 12 | G 1/4 | 0.5 - 10 bar | 1100 | 137.8 | 192.1 mm | 67.0 | 125.1 | 6 | 1 |
| K- 07 25 01 15 | G 3/8 | 0.5 - 10 bar | 1100 | 137.8 | 192.1 mm | 67.0 | 125.1 | 10 | 1 |
| K- 07 25 01 18 | G 1/2 | 0.5 - 10 bar | 3000 | 200.8 | 246.3 mm | 99.0 | 147.3 | 15 | 2 |
| K- 07 25 01 21 | G 3/4 | 0.5 - 10 bar | 3000 | 200.8 | 246.3 mm | 99.0 | 147.3 | 25 | 2 |
| K- 07 25 01 24 | G 1 | 0.5 - 10 bar | 11300 | 300.0 | 381,4 mm | 128.0 | 253.8 | 25 | 3 |